

## **INDOOR LEDWALL**





Indoor video walls can create a spectacular impact to passers-by and reinforce any brand communication. NSELED LED system delivers excellent picture quality even at close range and at a wide viewing angle.

## **FAST&EASY TO UPDATE**

NSELED LEDwalls are user-friendly. Thanks to an A4 controller, they support LAN, WIFI, USB and HDMI connection. A CLOUD allows you to upload content and update displays remotely.

With an Indoor LED screen you have the possibility to display high-resolution images and videos in public spaces such as exhibitions, museums, retail stores, theatres, education facilities and security monitoring rooms.





- Energy saving
- Long life span
- High image definition
- High-quality LED lamp beads





## **INDOOR LEDWALL SPECIFICATIONS**

| Indoor wall mounted WA series |                             |                             |                            |                             |  |  |
|-------------------------------|-----------------------------|-----------------------------|----------------------------|-----------------------------|--|--|
| Model Type                    | P2                          | P2.5                        | P3 076                     | P4                          |  |  |
| Application                   | Indoor                      | Indoor                      | Indoor                     | Indoor                      |  |  |
| Module size                   | 320*160mm                   | 320*160mm                   | 320*160mm                  | 320*160mm                   |  |  |
| Brightness                    | 1000 nit                    | 1000 nit                    | 800 nit                    | 800 nit                     |  |  |
| Scan                          | 1/40                        | 1/32                        | 1/26                       | 1/20                        |  |  |
| Remarks                       | 3840HZ (Hight Refresh Rate) | 3840HZ (Hight Refresh Rate) | 3840HZ (Hight Refresh Rate | 3840HZ (Hight Refresh Rate) |  |  |
|                               | with Magnet                 | with Magnet                 | with Magnet                | with Magnet                 |  |  |

| WA Series  |            |            |            |  |
|------------|------------|------------|------------|--|
| 640x480 mm | 640x640 mm | 320x640 mm | 960x480 mm |  |

| Indoor wall mounted WS series |                             |                             |                            |                             |  |  |
|-------------------------------|-----------------------------|-----------------------------|----------------------------|-----------------------------|--|--|
| Model Type                    | P1 953                      | P2 604                      | P2 976                     | P3 91                       |  |  |
| Application                   | Indoor                      | Indoor                      | Indoor                     | Indoor                      |  |  |
| Module size                   | 250*250mm                   | 250*250mm                   | 250*250mm                  | 250*250mm                   |  |  |
| Brightness                    | 1000 nit                    | 1000 nit                    | 1000 nit                   | 800 nit                     |  |  |
| Scan                          | 1/32                        | 1/32                        | 1/28                       | 1/16                        |  |  |
| Remarks                       | 3840HZ (Hight Refresh Rate) | 3840HZ (Hight Refresh Rate) | 3840HZ (Hight Refresh Rate | 3840HZ (Hight Refresh Rate) |  |  |
|                               | with Magnet                 | with Magnet                 | with Magnet                | with Magnet                 |  |  |

| WS Series  |             |             |  |  |
|------------|-------------|-------------|--|--|
| 500x500 mm | 1000x250 mm | 1000x500 mm |  |  |

NSELED Europe srl Via Marco d'Agrate, 41/B 20139 Milano Italia info@nseled.eu T. 02 40707210



For more information









