

OUTDOOR ADVERTISING NEWS STAND

NSELED news stand is a brand new advertising display that offers the latest achievement in LCD technology, bringing together a sleek design with peak performances.

Sunlight Readable

Brightness is paramount outdoors! These displays can boast commercial grade **Ultra High Brightness panels** (2,000 nit/m²), more than **5 times brighter** than a standard home TV. This allows easy **readability in direct sunlight**. An **ambient light sensor** will adjust the brightness of the screen according to surrounding light levels to offer **top performance in every weather condition** while optimizing energy consumption.

Temperature Control

The **internal air-conditioning** system keeps the panels and other internal components at the **optimum working temperature**, ensuring constant performance and a **long and reliable life** for your display in every outdoor environment.



Digital signage for outdoor advertising

Waterproof & lightning protection for constant performance in every environment.



Also available with
touchscreen display



Products data

		43"	49"	55"	65"	75"	86"	
Panel	Display Size (inch)	43"	49"	55"	65"	75"	86"	
	Resolution	1920x1080	1920x1080	1920x1080	1920x1080	3840x2160	3840x2160	
	Active Display Area (mm)	941x529	1073.5x603.0	1209.6x680.4	1428.5x803.5	1650.3x928.3	1938.2x1098.3	
	Aspect Ratio	16:09	16:09	16:09	16:09	16:09	16:09	
	Brightness (cd/m2)	2000 nit	2000 nit	2500 nit	2500 nit	2500 nit	2500 nit	
	Contrast Ratio (Type)	1000:1	1000:1	2000:1	2000:1	3000:1	3000:1	
	Viewing Angle (H/V)	178/178	178/178	178/178	178/178	178/178	178/178	
	Color	16.7M	16.7M	16.7M	16.7M	16.7M	16.7M	
Sound	Response time (G-to-G)	6ms	6ms	6ms	6ms	6ms	6ms	
	Operation Hour	24/7	24/7	24/7	24/7	24/7	24/7	
Power	Loud Speake	5W,80 (2sets)	5W,80 (2sets)	5W,80 (2sets)	5W,80 (2sets)	5W,80 (2sets)	5W,80 (2sets)	
	Type	Internal	Internal	Internal	Internal	Internal	Internal	
	Power Supply	AC 100-240 V-(+/- 10%) 50/60Hz						
Mechanical Spec	Power	100	120	150	260	280	360	
	Consumption	less than 0.5W	less than 0.5W	less than 0.5W	less than 0.5W	less than 0.5W	less than 0.5W	
	Max (W/h) Sleep mode Off mode	less than 0.5W	less than 0.5W	less than 0.5W	less than 0.5W	less than 0.5W	less than 0.5W	
Environmental	Protection Glass	Yes	Yes	Yes	Yes	Yes	Yes	
	Stand Type	Foot Stand	Foot Stand	Foot Stand	Foot Stand	Foot Stand	Foot Stand	
	Operating Temperature	-30°C - 50°C	-30°C - 50°C	-30°C - 50°C	-30°C - 50°C	-30°C - 50°C	-30°C - 50°C	
	Storage Temperature	-30°C - 50°C	-30°C - 50°C	-30°C - 50°C	-30°C - 50°C	-30°C - 50°C	-30°C - 50°C	
	Operating Humidit	10% - 80%	10% - 80%	10% - 80%	10% - 80%	10% - 80%	10% - 80%	
	Storage Humidit	5% - 95%	5% - 95%	5% - 95%	5% - 95%	5% - 95%	5% - 95%	
OS	Cooling System	Powerful Turbofan & cross flow fan/air condition (Optional)						
	Hypothermia protection	Heater (aluminium sheetwarmer) (Optional)						
	Android Media Player	Processor	Rockchip @ 3288 (1.8GHz, octa corer)					
		RAM	2G					
		Flash	8G EMM C					
		USB	USB2.0 HOST (x2)					
		LAN	10M/100M Ethernet (Network version screen only)					
		External memory	8GB SD card (up to 320)					
		Multimedia	Video (MPG, AVI, MP4, RM, RMVB, TS) - Image (JPG, GIF, BMP, PNG)					
		Media Resolution	1920*1080					
Wi-Fi		802.11b/g/n Ethernet (Network version screenonly)						
Operating System		Android 7.1						
Certification	Safety	CE ROHS						
Accessories	Included	Scheduling software, Remote control, Key, Power cable 5D card						
	Quality assurance	1 year						
	Type of packaging	Carton box/honeycomb box+ wooden case						



Sunlight Readable



24/7 Usage



Touch Screen Upgrade



Android Media Player



Vandal Proof



Integrated Temperature Control



Steel Enclosure



Water Proof

Weather Proofing

Lifting Bolt

Security Lock

Loudspeaker

Outdoor Enclosure

Designed with robust, **anti-corrosion casing** to shelter the display against the elements and vandalism.

With an **IP65 rating**, it keeps out humidity and all airborne particles. This display also features waterproof over molded AV connector.

The enclosures are made from mild steel and have **thermally toughened glass**.

